

REPLACED BY
ART 34 AMDT

WHAT IS CLAIMED IS:

1. A ball screw comprising:

a screw shaft having a ball rolling groove on an
outer periphery thereof;

5 a plurality of balls rollable along said ball
rolling groove;

a nut member engaged with said screw shaft through
said balls;

a lubricant supply mechanism provided at each axial
10 end of said nut member; and

a seal member provided outside said lubricant supply
mechanism;

wherein said lubricant supply mechanism has an
application member whose distal end is in sliding contact
15 with said ball rolling groove so that lubricant is
supplied to said ball rolling groove through said
application member, and

wherein an oil lip member is provided in a vicinity
of said application member with a predetermined gap
20 provided between itself and said application member; said
oil lip member having a distal end placed in sliding
contact with a surface of said ball rolling groove.

2. A ball screw according to claim 1, wherein said
oil lip member is secured to a mount portion of the
25 application member of said lubricant supply mechanism
through a leaf spring so that the distal end of said oil
lip member is always kept in sliding contact with the
surface of said ball rolling groove by elastic force of

REPLACED BY
ART 34 AMDT

said leaf spring.

3. A ball screw according to claim 1, wherein said oil lip member has a sliding contact portion that comes in sliding contact with the surface of said ball rolling
5 groove, said sliding contact portion being made of a wear-resistant resin material, and said sliding contact portion being integrally provided at a distal end of an oil lip body made of an elastic material,

said oil lip member being secured to a mount portion
10 of the application member of said lubricant supply mechanism through a support member so that a distal end of said sliding contact portion is always in sliding contact with the surface of said ball rolling groove.

4. A ball screw comprising:
15 a screw shaft having a ball rolling groove on an outer periphery thereof;

a plurality of balls rollable along said ball rolling groove;

a nut member engaged with said screw shaft through
20 said balls;

a lubricant supply mechanism that supplies lubricant to a part of the ball rolling groove located in said nut member; and

a seal member provided at each end of said nut
25 member;

wherein said seal member has an oil lip member whose distal end is always in sliding contact with a surface of said ball rolling groove.

REPLACED BY
ART 34 AMDT

5. A ball screw according to claim 4, wherein said oil lip member has a sliding contact portion that comes in sliding contact with the surface of said ball rolling groove, said sliding contact portion being made of a wear-resistant resin material, and said sliding contact portion being integrally provided at a distal end of an oil lip body made of an elastic material.